# With a true 2000W output and eco-friendly refrigerant, it sets a new standard for comfort in motorhomes and campers

Forget the limitations: **no inverters, no sockets, no worries**. OpenAir PLUS runs on a **12V battery and uses eco-friendly refrigerant**, delivering a more efficient and environmentally conscious experience.

The ideal temperature, whenever you need it. Thanks to Full Inverter technology across all components, you'll enjoy optimised performance and lower energy consumption.



## Travel freely on 12V - experience true innovation

OpenAir PLUS keeps your vehicle interior perfectly comfortable at all times. With new features such as the backlit interior panel and electric air diffusers, airflow is evenly distributed to ensure maximum comfort.

Make the most of your home on wheels.

# Proven quality **BERGSTROM**

Bergstrom, with **over 75 years of experience**, is a leader in manufacturing climate control systems for vehicles.

Our commitment to you and the environment focuses on continuous improvement in three key areas: innovation, manufacturing, and quality.

Certified quality ISO 9001/ISO 14001/IATF 16949







#### LEADER IN ELECTRIC AIR CONDITIONING FOR VEHICLES

T. + 34 - 918 775 840E. ventas@dirna.bergstrominc.comW. bergstromcaravaning.com/en/





## Power, comfort and efficiency, no cables, no limits

OpenAir PLUS cools your vehicle rapidly, now featuring electric flaps for more precise airflow control and an optimised design for improved energy efficiency.

Offers high-performance, energy-efficient cooling through advanced Full Inverter<sup>(\*)</sup> technology.

## Enjoy the perfect temperature wherever you go

Our systems are designed for true freedom seakers, those who want to enjoy maximum comfort in their vehicle on every adventure, without worrying about where they are.



## 12V

#### Without plugs or inverters.

It operates at 12V connected only to your vehicle's auxiliary battery.

# eco

#### With new ecological gas.

Closed circuit with non-toxic R-1234yf refrigerant gas.



#### **Total remote control**

Remote control with display included with the unit and intuitive mobile APP.





For roofs with a thickness between 30 and 60 mm.



#### Quick and easy installation

For motorhomes and campers. Skylights of 40x40cm or 50x70cm.



TECHNICAL CHARACTERISTICS	
Voltage	12 V
Cooling capacity in accordance with ISO 5151:T1	1250 W 2000 W
Electricity consumption when running in accordance with ISO 5151:T1 (*)	16 - 39 A - 1250 W 16 - 60 A - 2000 W
Average consumption	10A (24°C interior / 30°C exterior)
External unit dimensions (L x W x H)	786 x 986 x 200 mm
External unit weight	25.3 kg
Interior console dimensions (L x W x H)	520 x 520 x 50 mm
Interior console weight with fastening brackets	5.295 kg
Control panel	Touch panel with automatic flaps.
Remote control	Go with Backlit LCD Display
Adjustable intensity	RGB multicolour
Ideal vehicle length	Up to 7 m
Refrigerant	R-1234yf





#### **Backlit interior panel** Modern interior panel, with LED lighting up to 16 colours.

New electric diffusers

Upgraded interior flaps with

electric operation (AirSwing).

**K**•) **Different mounting positions** 

Allows selection from four different installation positions.