



60 KW AIR COOLED CHILLER (SLIMLINE STYLE)

BESTic⁺ - Bergstrom Energy Storage Thermal - intelligent cooling

FEATURES

- Liquid battery cooled design
- Additional Positive Temperature Coefficient (PTC) heater to assist in lower ambient temperatures
- High efficiency variable speed blower for precise air flow
- Variable speed DC compressor for precise temperature control
- High reliability
- Industrial grade design
- Ease of installation

TECHNICAL INFORMATION

- Input Power: 400 VAC & 480 VAC/3-phase/50Hz - 60Hz
- Communication: Modbus Protocol with RS485 signal level
- Refrigerant: R32
- Coolant: Glycol Solution
- IP Rating: IPx5

PERFORMANCE SPECIFICATIONS

- Cooling 60 kW (204,800 BTU/hr)
- PTC Heater: 24 kW (81,891 BTU/hr))

WEIGHTS & DIMENSIONS

- 400 kg (882 lbs)
- 1,200 mm L x 440 mm W x 2,400 mm H
(47 in L x 17 in W x 94 in H)



Bergstrom[®]

REV: 04-06-2025

<https://us.bergstrominc.com/battery-energy-storage-thermal-management-system/> | 2390 Blackhawk Road | Rockford, IL 61109 U.S.A. | 815.874.7821